8 IEC C13

19" Rack Power Distribution Units (PDU)

black

ARTICLE CODE WPN-PDU-I05-08

19-Inch 1U Rack PDU – 8 IEC C13 Outlets – Type L Plug



black COLOR	**1** UNIT	**ITA L (16A)** PLUG TYPE
8 NUMBER OF SOCKETS	**IEC C13** SOCKET TYPE	

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-PDU-I05-08

Technical data

COLOR	black
UNIT	1
PLUG TYPE	ITA L (16A)
NUMBER OF SOCKETS	8
SOCKET TYPE	IEC C13

Applications

- Applications section not available in the product description.

Main features

- Aluminum structure
- 8 outlets IEC C13
- 19” rack mount – occupies 1 unit (1U)
- Illuminated switch with protective cover
- Child protection
- Maximum voltage: 250V / 3500W
- H05VV-F 3G 1.5 mm² cable – length 2 m
- Plug type: L (ITA 16A)

PRODUCT IDENTIFICATION

Code: WPN-PDU-I05-08

EAN: 8056045871435

ONLINE PRODUCT PAGE

Scan the QR code

Additional details

Rack 19” 1U PDU – 8 Outlets IEC C13 with Protected Switch - Type L (ITA) Plug

The WP RACK 19” 1U rack PDU is designed to distribute electrical power safely and efficiently to servers, switches and network equipment installed inside 19” rack cabinets.

Manufactured with a high-quality aluminum structure, it guarantees robustness, reliability and long service life even in high-density IT and industrial environments.

Thanks to its compact dimensions (1U) and a depth of only 45 mm, it can be easily integrated into the rack without compromising the usable space for equipment.

Safe and Reliable Power Supply

The PDU provides stable AC power to connected devices, ensuring operational continuity and organized management of electrical connections.

It is equipped with:

- Illuminated switch with protective cover, which prevents accidental shutdown of the power supply
- Child protection, for increased safety in professional environments

IEC C13 Outlets for IT Equipment

The PDU is equipped with 8 IEC C13 outlets, designed to power servers, switches, UPS systems and professional devices with IEC C14 connectors.

IEC C13 outlets ensure:

- compatibility with international IT standards
- secure and stable connections
- seamless integration in data centers and professional environments

Ideal for IT and networking infrastructures.

Flexible Installation

The PDU can be installed in different configurations thanks to the rotatable mounting brackets:

- 1U 19” – horizontal mounting
- 0U – vertical mounting
- under-desk installation
- wall installation

Additional details

This versatility makes it suitable for multiple installation scenarios in IT and networking infrastructures.

Robust Aluminum Structure

The durable aluminum structure protects the internal components and resists impacts and abrasions even in demanding industrial environments, helping to extend the product’s service life over time.

Material Quality and Construction Reliability

WP RACK PDUs stand out for the use of selected materials and construction solutions designed for long-term durability.

The plastic parts are made with 100% new materials, avoiding the use of regenerated or second-melt plastics that can become more rigid and fragile over time.

The internal connections between the outlets are made of 100% pure copper, ensuring better electrical conductivity and greater reliability compared to CCA (Copper Clad Aluminum) solutions.

To reduce the risk of electromagnetic interference inside the rack cabinet, the PDUs integrate internal cable shielding, helping to maintain operational stability even in high-density IT environments.