PROFESSIONAL 19" RNA NETWORK RACK CABINET, 22U…

Network Cabinets

black

ARTICLE CODE WPN-RNA-22608-B

Professional 19" RNA network rack cabinet, 22U 600×800 mm, supplied assembled, with tempered glass front door, load capacity up to 800 kg and 4 depth-adjustable mounting rails.

The professional WP RACK RNA series network rack cabinet is designed for IT, networking, telecommunications and data-room installations requiring strength, flexibility and easy equipment access. This 22U version with a 600×800 mm footprint is supplied assembled for quick installation.

The supporting frame is made from 2 mm steel, with 1.5 mm steel panels, providing high rigidity and a load capacity up to 800 kg. The tempered glass front door with 1.5 mm metal frame opens up to 180° and includes a handle with key lock.



1116 mm HEIGHT	**600 mm** WIDTH	**800 mm** DEPTH
black COLOR	**22** UNIT	**Assembled** PROVIDED

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-RNA-22608-B

Technical data

HEIGHT	1116 mm
WIDTH	600 mm
DEPTH	800 mm
COLOR	black
UNIT	22
PROVIDED	Assembled
INSTALLATION	Floor-standing

Applications

- Ideal for data rooms, enterprise networks, telecommunications, video surveillance, IT infrastructure and professional installations requiring high load capacity and easy equipment access.

Main features

- WP RACK RNA series professional 19" network rack cabinet
- Height: 22U
- Dimensions WxDxH: 600×800×1166 mm
- Supplied assembled
- 2 mm steel supporting frame
- 1.5 mm steel panels
- Tempered glass front door, opening up to 180°
- Removable side panels and rear door with locking system
- 4 numbered 19" mounting rails, depth adjustable
- Top and bottom cable entries with removable covers
- Roof preparation for 120 mm fans or ventilation kit, not included
- Load capacity up to 800 kg

PRODUCT IDENTIFICATION

Code: WPN-RNA-22608-B

EAN: 8056045871244

ONLINE PRODUCT PAGE

Scan the QR code

Additional details

Main features - continued

- 4 casters, 2 with brakes
- 4 leveling feet
- Earthing kit included
- 20 sets of screws and cage nuts included
- Weight: 67.2 kg
- Colour: black RAL 9005
- IP20 protection rating

Front door

The tempered glass front door allows visual inspection of installed equipment without opening the cabinet. Opening up to 180° and the key lock simplify installation and maintenance while helping protect the equipment.

Rear door

The removable rear door simplifies access to cabling and equipment during installation and maintenance. Its locking system helps keep the cabinet interior protected.