19" RNV SERIES AUDIO-VIDEO RACK CABINET, 42U 60…

Audio-video Cabinets

black

ARTICLE CODE WPN-RNV-42606-B

19" RNV series audio-video rack cabinet, 42U 600×600 mm, supplied assembled with ventilated shelves and blanking panels, rear door with dedicated cable-entry slots and load capacity up to 800 kg.

The professional WP RACK RNV series audio-video rack cabinet is designed as a ready-to-use solution for AV installations in home theatres, recording studios, hotels, wellness centres, meeting rooms and professional environments.

The 2 mm steel supporting frame and 1.5 mm steel panels provide high rigidity and a load capacity up to 800 kg. The tempered glass front door opens up to 180° and is fitted with a handle and key lock.



2055 mm HEIGHT	**600 mm** WIDTH	**black** COLOR
42 UNIT	**Assembled** PROVIDED	**Floor-standing** INSTALLATION

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-RNV-42606-B

Technical data

HEIGHT	2055 mm
WIDTH	600 mm
DEPTH	600 mm
COLOR	black
UNIT	42
PROVIDED	Assembled
INSTALLATION	Floor-standing

Applications

- Home theatres, recording studios, hotels, wellness centres, conference rooms and professional audio-video installations requiring organized equipment and cable management.

Main features

- WP RACK RNV series 19" audio-video rack cabinet
- Height: 42U
- Dimensions WxDxH: 600×600×2055 mm
- Supplied assembled
- 2 mm steel supporting frame
- 1.5 mm steel panels
- Tempered glass front door, opening up to 180°, with key lock
- Removable lockable side panels
- Removable lockable rear door with cable-entry slots
- Cable entry from bottom, roof and rear door
- Roof preparation for 120 mm fans or ventilation kit, not included
- 4 numbered 19" mounting rails, depth adjustable

PRODUCT IDENTIFICATION

Code: WPN-RNV-42606-B

EAN: 8054392612824

ONLINE PRODUCT PAGE

Scan the QR code

Additional details

Main features - continued

- Load capacity up to 800 kg
- 4 casters, 2 with brakes
- 4 leveling feet
- Earthing kit included
- 40 sets of screws and cage nuts included
- Weight: 122 kg
- Colour: black RAL 9005
- IP20 protection rating

Included equipment 42U

Quick-release blanking panels: 2×3U, 2×2U, 2×1U

- 2 × ventilated shelf 1U, 300 mm deep, 25 kg load, 2-point mounting
- 2 × ventilated shelf 2U, 350 mm deep, 35 kg load, 2-point mounting
- 3 × ventilated shelf 1U, 350 mm deep, 45 kg load, 4-point mounting