PROFESSIONAL 19" RSA 27U 600×1000 MM ASSEMBLED...

Server Cabinets

black

ARTICLE CODE WPN-RSA-27610-B

Professional 19" RSA 27U 600×1000 mm assembled server rack cabinet, with perforated steel front door, blind rear door and load capacity up to 1000 kg. Bottom panel sold separately.

Professional 19" RSA series server rack cabinet with 27U and overall dimensions of 600×1000×1388 mm. The reinforced steel structure is designed to offer a robust solution, with a load capacity up to 1000 kg, for professional installations that require stability and reliability.

This version is supplied assembled. The cabinet is supplied without the bottom panel as standard, which is sold separately, and includes 4 reinforced casters, leveling feet, grounding kit, top modular cable entry with cover and provision for 120 mm fans or a dedicated ventilation kit on the top.



1388 mm HEIGHT	**600 mm** WIDTH	**1000 mm** DEPTH
black COLOR	**27** UNIT	**Assembled** PROVIDED

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-RSA-27610-B

Technical data

HEIGHT	1388 mm
WIDTH	600 mm
DEPTH	1000 mm
COLOR	black
UNIT	27
PROVIDED	Assembled
INSTALLATION	Floor-standing

Applications

- Data centers, server rooms, professional IT infrastructures, telecommunications and enterprise installations that require high load capacity and effective equipment ventilation.

Main features

- Height: 1388 mm
- Width: 600 mm
- Depth: 1000 mm
- Color: black
- Unit: 27
- Provided: Assembled
- Installation: Floor-standing

PRODUCT IDENTIFICATION

Code: WPN-RSA-27610-B

EAN: 8056045871329

ONLINE PRODUCT PAGE

Scan the QR code

Additional details

Main Features

- Professional 19" server rack cabinet
- 27U height
- 600×1000×1388 mm dimensions
- Perforated steel front door
- Blind rear door
- Front door handle with 3-point locking system
- Load capacity up to 1000 kg
- 4 reinforced casters
- Bottom panel not included, sold separately
- 2 mm solid steel structure with 1.5 mm steel side panels
- Hinged and removable side panels with inside locking system
- 4 numbered front rails with adjustable depth
- Leveling feet included
- Grounding kit included
- Modular top cable entry with cover
- Provision for top ventilation with 120 mm fans or dedicated kit
- 40 screw sets included
- Black RAL 9005 finish
- IP20 protection rating

Front Door

The perforated steel front door helps improve airflow inside the cabinet and is equipped with a handle and 3-point locking system for secure closure and practical use.

Rear Door

Additional details

The blind rear door completes the cabinet configuration and helps protect the installed equipment.