

PROFESSIONAL 19" RSA 42U 800×1000 MM ASSEMBLED...

Server Cabinets

black

ARTICLE CODE WPN-RSA-42810-B

Professional 19" RSA 42U 800×1000 mm assembled server rack cabinet, with perforated steel front door, blind rear door and load capacity up to 1000 kg. Bottom panel sold separately.

Professional 19" RSA series server rack cabinet with 42U and overall dimensions of 800×1000×2055 mm. The reinforced steel structure is designed to offer a robust solution, with a load capacity up to 1000 kg, for professional installations that require stability and reliability.

This version is supplied assembled. The cabinet is supplied without the bottom panel as standard, which is sold separately, and includes 4 reinforced casters, leveling feet, grounding kit, top and bottom cable entry, and provision for 120 mm fans or a dedicated ventilation kit on the top.



2055 mm

HEIGHT

800 mm

WIDTH

1000 mm

DEPTH

black

COLOR

42

UNIT

Assembled

PROVIDED

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-RSA-42810-B

Technical data

HEIGHT	2055 mm
WIDTH	800 mm
DEPTH	1000 mm
COLOR	black
UNIT	42
PROVIDED	Assembled
INSTALLATION	Floor-standing

Applications

- Data centers, server rooms, professional IT infrastructures, telecommunications and enterprise installations that require high load capacity and effective equipment ventilation.

Main features

- Height: 2055 mm
- Width: 800 mm
- Depth: 1000 mm
- Color: black
- Unit: 42
- Provided: Assembled
- Installation: Floor-standing

PRODUCT IDENTIFICATION

Code: WPN-RSA-42810-B

EAN: 8056045875563

ONLINE PRODUCT PAGE

Scan the QR code



Additional details

Main Features

- Professional 19" server rack cabinet
- 42U height
- 800×1000 mm dimensions
- Perforated steel front door
- Blind rear door
- Front door handle with 3-point locking system
- Load capacity up to 1000 kg
- 4 reinforced casters
- Bottom panel not included, sold separately
- 2 mm steel structure with 1.5 mm side panels
- Removable side panels with inside locking system
- 4 numbered front rails with adjustable depth
- Leveling feet included
- Grounding kit included
- Top and bottom cable entry
- Provision for top ventilation with 120 mm fans or dedicated kit
- 40 screw sets included
- Black RAL 9005 finish
- IP20 protection rating

Front Door

The perforated steel front door helps improve airflow inside the cabinet and is equipped with a handle and 3-point locking system for secure closure and practical use.

Rear Door

Additional details

The blind rear door completes the cabinet configuration and helps protect the installed equipment.