PROFESSIONAL 19" RSA 42U 800×1000 MM SERVER RAC…

Server Cabinets

black

ARTICLE CODE WPN-RSA-42812-BS

Professional 19" RSA 42U 800×1000 mm server rack cabinet supplied disassembled in flat-pack version, with perforated steel front door, blind rear door and load capacity up to 1000 kg. Bottom panel sold separately.

Professional 19" RSA series server rack cabinet with 42U and overall dimensions of 800×1200×2055 mm. The reinforced steel structure is designed to offer a robust solution, with a load capacity up to 1000 kg, for professional installations that require stability and reliability.

This version is supplied disassembled in flat-pack version, a practical solution that makes transport, handling and installation easier in technical rooms with limited access. The cabinet is supplied without the bottom panel as standard, which is sold separately, and includes 4 reinforced casters, leveling feet, grounding kit, top and bottom cable entry, and provision for 120 mm fans or a dedicated ventilation kit on the top.



2055 mm HEIGHT	**800 mm** WIDTH	**1200 mm** DEPTH
black COLOR	**42** UNIT	**Unassembled** PROVIDED

PROFESSIONAL TECHNICAL DATASHEET

Technical information

WPN-RSA-42812-BS

Technical data

HEIGHT	2055 mm
WIDTH	800 mm
DEPTH	1200 mm
COLOR	black
UNIT	42
PROVIDED	Unassembled
INSTALLATION	Floor-standing

Applications

- Data centers, server rooms, professional IT infrastructures, telecommunications and enterprise installations that require high load capacity and effective equipment ventilation.

Main features

- Height: 2055 mm
- Width: 800 mm
- Depth: 1200 mm
- Color: black
- Unit: 42
- Provided: Unassembled
- Installation: Floor-standing

PRODUCT IDENTIFICATION

Code: WPN-RSA-42812-BS

EAN: 8032958189652

ONLINE PRODUCT PAGE

Scan the QR code

Additional details

Main Features

- Professional 19" server rack cabinet
- 42U height
- 800×1200 mm dimensions
- Perforated steel front door
- Blind rear door
- Front door handle with 3-point locking system
- Load capacity up to 1000 kg
- 4 reinforced casters
- Bottom panel not included, sold separately
- Supplied disassembled in flat-pack version
- 2 mm steel structure with 1.5 mm side panels
- Removable side panels with inside locking system
- 4 numbered front rails with adjustable depth
- Leveling feet included
- Grounding kit included
- Top and bottom cable entry
- Provision for top ventilation with 120 mm fans or dedicated kit
- 40 screw sets included
- Black RAL 9005 finish
- IP20 protection rating

Front Door

The perforated steel front door helps improve airflow inside the cabinet and is equipped with a handle and 3-point locking system for secure closure and practical use.

Additional details

Rear Door

The blind rear door completes the cabinet configuration and helps protect the installed equipment.